## CLAIMS

## What is claimed is:

- 1 1. A hard disk drive, comprising:
- 2 a base plate;

5

- 3 a spindle motor coupled to said base plate;
- a disk coupled to said spindle motor;
  - an actuator arm mounted to said base plate;
    - a voice coil motor coupled to said actuator arm;
    - a head coupled to said actuator arm;
    - a cover plate attached to said base plate to create an internal cavity that contains said head;
      - a heater located within said internal cavity;
      - a temperature sensor that can sense a temperature of
- 12 said internal cavity; and,
- a control circuit to control said heater to maintain a
- 14 temperature of internal cavity to be no less than a
- 15 threshold temperature.
  - 1 2. The hard disk drive of claim 1, wherein said
  - 2 control circuit includes an amplifier coupled to said

- 1 The hard disk drive of claim 1, wherein said heater
- 2 is coupled to said base plate.
- 1 The hard disk drive of claim 2, wherein said
- 2 control circuit includes a switch coupled to said comparator and said amplifier.
  - 5. The hard disk drive of claim 1, wherein the threshold temperature is approximately 10-15°C.
  - 6. The hard disk drive of claim 1, further comprising a register that stores the threshold value.
- 5 A hard disk drive, comprising: 7.
- 6 a base plate;
- 7 a spindle motor coupled to said base plate;
- 8 a disk coupled to said spindle motor;
- 9 an actuator arm mounted to said base plate;
- 10 a voice coil motor coupled to said actuator arm;

£.4.

- a head coupled to said actuator arm and said disk;
- 12 a cover plate attached to said base plate to create an
- 13 internal cavity that contains said head;

less than a threshold temperature.

- heater means for heating said internal cavity;
- 15 temperature sensor means for sensing a temperature of
- 16 said internal cavity; and,
- 17 control circuit means for controlling said heater to
- 18 maintain a temperature of said internal cavity to be no  $\frac{1}{2}$ 
  - 8. The hard disk drive of claim 7, wherein said control circuit means includes an amplifier coupled to said

heater and a comparator coupled to said amplifier and said

- temperature sensor means.
- 9. The hard disk drive of claim 7, wherein said heater
- 2 means is coupled to said base plate.
- 1 10. The hard disk drive of claim 8, wherein said
- 2 control circuit means includes a switch coupled to said
- 3 comparator and said amplifier.

- 1 11. The hard disk drive of claim 7, wherein the
- 2 threshold temperature is approximately 10-15°C.
- 3 12. The hard disk drive of claim 7, wherein said
- 4 control circuit means includes a register that stores the
- 5 threshold value.
  - 13. A method for controlling a temperature of a hard disk drive internal cavity, comprising:
  - sensing a temperature of a hard disk drive internal cavity; and,
  - activating a heater if the sensed temperature is less than a threshold value.
- 1 14. The method of claim 13, deactivating the heater if
- 2 the sensed temperature is at least the threshold value.
- 1 15. The method of claim 13, wherein the sensed
- 2 temperature is compared with a threshold value that is
- 3 stored in a register.

- 1 16. The method of claim 13, using exist temperature
- 2 sensing method in pre-amplifier or read/write chip.